

Telehandler / Zoom Boom

Used Telehandler Lancaster - Telehandlers are commonly known by a variety of names such as Cherry pickers, telescopic handlers, boom lifts and teleporters. These machines are utilized in agriculture and many different industries. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. The operator can utilize a variety of attachments at the end of the articulating boom to complete different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The main telehandler attachment is the pallet forks. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. Telehandlers allow cargo pallets to be transported from trailers and placed on racking, rooftops or other difficult to reach locations. Normally, high rooftop applications would require the use of a crane; however, telehandlers can complete this task more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Moving items from unreachable locations that cannot be completed with a backhoe loader or wheeled loader give telehandlers a huge advantage. Telehandlers are beneficial for applications that would usually require a loading ramp or conveyor since they are capable of directly accessing trailers with high sides and hoppers. Using one machine to finish numerous jobs saves storage space, money and time. Telehandler machines can work in conjunction with a crane jib. Various attachments may be used including rotators, dirt buckets, grain buckets and power booms. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. Conversely, the main advantage of this machine doubles as its' largest limitation. The boom raises or extends with heavy loads, acting as a lever. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. A 5000 lb. capacity telehandler could lift 400 lbs. safely while fully extended with a retracted boom in conjunction with a low boom angle. Raising the same piece of equipment 70 degrees could allow this machine with a five thousand pound lift capability and retracted boom to support up to ten thousand pounds. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. There are sensors and computers available on newer models. The operator is warned and even cut off further control input once the limits of the telehandler are surpassed. The lifting capacity is enhanced by front stabilizers that maximize the lifting capacity from a stationary position. Another option is a stabilizing rotary joint between lower and upper frames, often referred to as a mobile crane that can additionally utilize a bucket. There are many models of telehandlers differing in size, weight, boom designs and reach. Telehandlers that weigh 11,000 pounds or less fall into the compact category. Compact units have a two-stage boom compared to larger machines that feature three or four boom designs. Compact models rely on a low pivot boom to facilitate better cab visibility as the operator transports loads. There are narrower and smaller dimensions offered with the compact telehandler. Compact telehandlers have a reach capacity ranging between 13 to 20 feet with a lift capacity ranging from 5k to 7k pounds. The versatility of the compact telehandler makes it popular in a variety of applications. It may be used as a tool carrier or a pick and place machine. Compact units are ideal for cramped locations. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. Telehandlers can enter internal building access in hard-to-reach locations. Compact telehandlers are used in many applications including nurseries, erecting steel, multi-story construction, masonry, strip malls, garages and similar jobs. Agri-business and farming applications rely on telehandlers for a variety of jobs. Telehandlers can be found

with two and four-wheel drive and crab steering capabilities. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. Four-wheel drive units can travel over harder terrain while offering a tighter turning radius. Crab steering enhances the units' maneuverability while allowing each set of wheels to move forty-five degrees to the right or left. Compact telehandlers have numerous cab environments to choose from. On entry-level models, there is a rollover cage for added safety. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Compact units feature spacious cab accommodations to keep operators totally comfortable. Additional options including satellite radio, air conditioning, armrests, cup holders, suspension seats and tilt steering are available. The numerous attachment options are facilitated with high-pressure and high-flow auxiliary hydraulics. These attachments increase the functions the machine is capable of. Ground engaging work is often completed by compact units. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer attachments are being made for versatility and other compact telehandler designs.