

Terminal Tractor/Yard Spotter

Used Yard Spotter Lancaster - Tow tractors are a common piece of industrial equipment used in large buildings, arenas, warehouses, airports and manufacturing plants for moving loads horizontally. They go by different names including tow tugs and towing tractors. They are capable of towing several trailers in a train formation. Certain tow tractors can transport helicopters and giant airplanes for the purpose of positioning inside and outside airport hangars and terminals. Tractive effort is how these machines transport loads. Tractive effort refers to the total amount of traction a vehicle deploys on the ground. Tractive effort says that the heavier the load, the more tractive effort is required. Based on this principle, the tow tractor works by lifting a part of the load it is towing while making sure the load's wheels remain on the ground. The tractive effort is increased by the unit's hydraulic mast. This has been engineered to produce downforce on the drive wheel directly under the mast. The tow tractor is capable of transporting very heavy and large loads thanks to the traction it provides. Types of Tow Tractors Heavy-duty tow tractors and load carriers are two types of tow tractors. Load Carriers Many industries including airport baggage divisions, manufacturing, parcel transportation and e-commerce rely on moving items of various sizes to and from different locations. Tow tugs and load carriers easily transport single items that have been deposited on wheeled platforms and move them with ease. The category that load carrier tow tractor models fall into includes forklift trucks, cranes and pallet jacks. Load carrier tow tugs do not transport items from high places such as shelves or platforms. They only move cargo at ground level. In order to be ready for transport, items must be secured on a wheeled platform or already on wheels to use the tow tractor. The wheeled platforms are called bogies, trollies or skates. The tow tug is attached to the trolley similar to train cars being attached to a locomotive. Generally, the steel coupling on the tow tug's male-end joins to the front trolley's female-end. The trolley's back portion has a male-end steel coupling that can be used to connect a variety of trollies to a single tug. Tow tractors are capable of moving many machines in a variety of conditions. The availability of many different types of trollies also allows for greater customization in transporting items. Trollies can connect together and are compatible. Different kinds of trollies can be maneuvered in a single train, creating flexible transport options. Load carrier tow tractors deliver a clear view for the operator which can be better than relying on forklifts. Additionally, load carrier tow tractors move their units in a forward-only way and this drastically decreases safety concerns associated with forklifts traveling in reverse. This is vital for safety-sensitive places including airports and manufacturing facilities. It is more economical to tow multiple items when possible with a tug than using a forklift truck to transport single items. Tugs are easy to move and safe to use. The operator doesn't require a license, which is another benefit compared to forklifts. Tow tractor operators do not need licenses since they don't lift loads off of the ground. There are three subtypes of load carrier tow tractors: 1. Pedestrian; 2. Stand-in; and 3. Rider-seated. Pedestrian Tow Tractors A walk-behind model that can transport wheeled loads is called a pedestrian tow tractor. These machines may go by the names of electric hand tug, electric tugger, electric tug or tow tractor. These compact machines are simple to use and can maneuver easily. Stand-in Tow Tractors The most common design for businesses that rely on horizontal manufacturing transport and order picking are stand-in tow tractors. Stand-in tow tractors feature a tinier footprint compared to rider-seated editions and they offer a safe driver platform. Rider-Seated Tow Tractors Rider-seated tow tractors are similar to stand-in models except they offer a seated platform for the operator. Rider-seated models are used for moving loads longer distances. They are popular for airport luggage transport to move checked baggage from the check-in counter to the aircraft parked at the terminal. Rider fatigue is decreased with sit-down units for more efficiency and productivity. Heavy Duty Tow Tractors In the aviation industry, large passenger and cargo planes usually employ the concept of pushback. Pushback refers to the process of pushing an aircraft back from an airport terminal by some means other than the aircraft's own power. Pushback is achieved by employing pushback tugs or pushback tractors. Pushback

tractors are built with a low-profile to allow them to move underneath the nose of the aircraft so that it can attach. Enough ground friction is required to move the weighted aircraft, so these models need to be heavy themselves. A common tractor for moving large aircraft can weigh in up to fifty-four tons. Their driver's cab has the ability to be lowered and raised for increased visibility during reversing. The unit is called a pushback tow tractor or pushback tug but it is additionally used to move aircraft in situations where taxiing is not safe or practical including into and outside of aircraft maintenance. The pushback tow tractors come in two subtypes, the towbarless and the conventional. Conventional Pushback Tow Tractors Conventional tugs use a tow bar to connect the tug to the nose landing gear of the aircraft. The tow bar is fixed laterally at the nose landing gear, but may move slightly vertically for height adjustment. The tow bar that attaches to the tug can pivot vertically and laterally. The tow bar functions as a sizeable lever to facilitate nose landing gear rotation. Each aircraft type has a unique tow fitting so the towbar also acts as an adapter between the standard-sized tow pin on the tug and the type-specific fitting on the aircraft's landing gear. On heavy towbars for large aircrafts, the towbar rides on its own wheels when not connected to an aircraft. The hydraulic jacking mechanism is attached to the wheels, allowing the towbar to lift to the correct height in order to mate with the tug and the aircraft. The same means are used in reverse during the pushback process to raise the towbar wheels from the ground. The towbar can be connected at the front or the rear of the tractor, depending on whether the aircraft will be pushed or pulled. Towbarless Pushback Tow Tractors Towbarless tractors, as their name suggests, don't rely on a towbar. Instead, these machines scoop up the nose landing gear to lift it off of the ground so the tug can move the plane. This allows better control of the aircraft and higher speeds; it may also eliminate the need to have a worker in the cockpit to apply the aircraft's brakes. Simplicity is the main advantage of the towbarless tugs since it is not necessary to maintain a variety of towbars. Directly connecting the tug to the landing gear allows operators to have better responsiveness and control while moving the aircraft.